

Specification Sheet

Description **Fuelchief Farm Tank**

Part No **FC Over-Head**



When it comes to storing fuel on site for the agri-sector, many items need to be considered such as location, size of farm, fuel usage on your farm and how regularly fuel is delivered to the farm.

Fuelchief Farm Tanks are for farms across Australia, New Zealand and the rest of the world, they act as a storage solution for petrol or diesel that needs to be accessed on or near agricultural sites. Fuelchief has released a series of farm tanks for the market that complies with AS1940, AS1692 and AS1657 requirements (API Australia) and NZ WorkSafe standards. Below are some of these tanks key features:

- ♥ 900 and 1500L capacities with split models available
- ♥ Safe 4-legged design made of robust material including compliant platform ladder
- ♥ Pad lockable ball valve and clear bowl filter
- ♥ Gravity feed with 4 meter hose with manual nozzle
- ♥ Easy-to-follow assembly instructions
- ♥ Can be easily stocked and shipped
- ♥ Light weight design
- ♥ 3" filling point and calibrated dipstick
- ♥ Manufactured by robotic processes, ensuring precision placement of parts
- ♥ Durable to withstand rural conditions
- ♥ Suitable for storing both petrol and diesel

Model No.	Dimensions (assembled)	Capacity (total)	Capacity (SFL)	Weight (empty)
FC6030-OH-K	160 cm (l) x 120cm (w) (ladder & vent included)	600/300L	580/290L	270kg
FC90-OH-K	160 cm (l) x 120cm (w) (ladder & vent included)	925L	900L	230kg
FC1050-OH-K	235 cm (l) x 120cm (w) (ladder & vent included)	1000/500L	970/485L	335kg
FC150-OH-K	235 cm (l) x 120cm (w) (ladder & vent included)	1500L	1470L	295kg

Below are the WorkSafe farm tank standards for New Zealand (above) and the API standards for Australia (below)

