

# Specification Sheet

Description **Fuelchief DCD450**

Part No **DCD450**



A robust design, from the ground up, the DCD450 tank features an improved inner tank wall with no internal bracing. Fully compliant with the EPA requirements for the storage of diesel.

The largest of the DC range, this is packed with all the standard Fuelchief features, plus thicker tank walls for added strength, the DCD450 is the choice for large operations needing to guarantee the security and reliability of their fuel supply. Below are some of the key features of this product:

- ♥ 42,000L (total capacity) model with large secure cabinet to house all pumps and equipment
- ♥ Full height access door with 3-way locking system and anti-levering design for extra security
- ♥ Cabinet has access hatch through roof to allow safe servicing of tank vent
- ♥ Hempel C4-H Marine grade paint system
- ♥ Lockable access door to fuel management terminal, switching and dry-break coupling
- ♥ Spill sump in cabinet base to contain spillage or drips
- ♥ Improved inner tank design with no internal bracing
- ♥ 6mm inner and outer tank material thickness
- ♥ Sloped floor in inner tank for better water catchment and recovery
- ♥ Water inspection and suction port housed under lockable hatch
- ♥ 2 x large access manholes for maintenance and inspection of inner tank
- ♥ Extra feed and return ports for running auxiliary equipment
- ♥ Lockable fill point with integrated dipstick
- ♥ Offset fill pipe with Todo Dry-Break coupling for rapid refueling
- ♥ 1100 LPM rated & approved overfill prevention valve for safe filling and accident prevention
- ♥ Base of tank sealed in an anti-rust underseal

Ext Dimensions (w,d,h)	Capacity (total)	Capacity (safe)	Weight (empty)
2270 x 11866 x 2500mm	42,000L	40,860L	11,600kg
Design Approval	Design Standard	Inner Tank	Outer Tank
TNK 16007	AS1692	6mm	6mm
*Due to custom nature of tank, weight may vary depending on application and design, does not include ladder in overall length or width			

