

Specification Sheet

Description **Fuelchief DC50**

Part No **DC50**



The DC50 is the tank that sits in half a car space and takes up less than 3.5m2. Occupying such a small footprint makes it a great solution for those operations that have limited room available, yet still need fast and reliable access to fuel.

Our most popular model comes complete with tank vent, contents gauge and dipstick. The sloping floor and water suction port ensures easy water catchment and removal. Below are some of the key features of this tank:

- ♥ 4,629 SFL model with large secure cabinet to house all pumps and equipment
- ♥ Full height access door with 3-way locking system and anti-levering design for extra security
- ♥ Cabinet has access hatch through roof to allow safe servicing of tank vent
- ♥ Hempel C4-High Marine grade paint system
- ♥ Spill sump in cabinet base to contain spillage
- ♥ Improved inner tank design with no internal bracing for safe servicing
- ♥ Sloped floor in inner tank for better water catchment and recovery
- ♥ Water inspection and suction port housed under lockable hatch
- ♥ Large access manhole for maintenance and inspection of inner tank
- ♥ Extra feed and return ports for running auxiliary equipment
- ♥ Lockable fill point with integrated dipstick
- ♥ Offset fill pipe with Todo Dry-Break coupling for rapid refuelling
- ♥ 1100 LPM rated & approved overfill prevention valve for safe filling and prevention of accidents
- ♥ Base of tank sealed in an anti-rust underseal

Ext Dimensions (w,d,h)	Capacity (total)	Capacity (safe fill)
1150 x 2996 x 2550mm	5,000L	4,629L
Design Approval	Design Standard	Weight (empty)
TNK 15024	AS1692	1,600kg
*Due to custom nature of tank, weight may vary depending on application and design, does not include ladder in overall length or width		