

Specification Sheet

Description **Fuelchief DCD100**

Part No **DCD100**



The DCD100 is a deluxe and unique tank that only takes up a car parking space, which is impressive. Occupying such a small footprint makes the DCD100 a popular choice and a great solution for those operations that have limited room available, yet still need fast and reliable access to fuel. Below are some of the key features of this product.

- ♥ 10,450L total capacity model with large secure cabinet to house all pumps and equipment
- ♥ Full height access door with 3-way locking system and anti-levering design for extra security
- ♥ Cabinet has access hatch through roof to allow safe servicing of tank vent
- ♥ Hempel C4-High Marine grade paint system
- ♥ Lockable access door to fuel management terminal, switching and dry-break coupling
- ♥ Spill sump in cabinet base to contain spillage
- ♥ Improved inner tank design with no internal bracing
- ♥ Sloped floor in inner tank for better water catchment and recovery
- ♥ Water inspection and suction port housed under lockable hatch
- ♥ Large access manhole for maintenance and inspection of inner tank
- ♥ Extra feed and return ports for running auxiliary equipment
- ♥ Offset fill pipe with Todo Dry-Break coupling for rapid refuelling
- ♥ Lockable fill point with integrated dipstick
- ♥ 1100 LPM rated & approved overfill prevention valve for safe filling and prevention of accidents
- ♥ Base of tank sealed in an anti-rust underseal

Ext Dimensions (w,d,h)	Capacity (total)	Capacity (safe fill)	Weight (empty)
2310 x 2996 x 2550mm	10,450L	9,900L	3,620kg
Design Approval	Tank Design Standard	Tank Design Standard	
TNK 15025	AS1692	AS1657	

*Due to custom nature of tank, weight may vary depending on application and design, does not include ladder in overall length or width

