

Specification Sheet

Description TransCube Global 10TCGCAB



The Fuelchief TransCube 10TCGCAB is a 110% bunded transportable tank, that covers multiple diesel storage applications across multiple industries. Below are some key features:



- 960 litre model can be transported full of diesel without the need for ADR driver training.
- Featuring a large single lockable cabinet to house all pumps and equipment
- Easily stacked 2 high (full), 3 high (empty) to reduce storage space requirements.
- Access manhole for maintenance and inspection of inner tank.
- Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the TransCube 10TCGCAB full of fuel.
- Secure lockable access hatch to house pumps (electric and hand!) and feed and return connections for up to 3 generators.
- Ability to supply fuel for up to 3 generators and refuel plant machinery all at the same time.
- Sized to stack inside shipping containers and across truck beds providing economical transportation.
- Protective galvanised framework preventing damage to tank, paintwork and decals.

Specifications

Standard Tank Fittings: 3"Fill Point: 2" Fill Point: Gauge: Pressure Vacuum Vent: Breather Vent: 1 x ¾" Pump Feed: 1 x %" Generator Feed & Return: 1 x 1%" Suction port: 1 x %" Socket: Inspection Manhole: Pump Bracket

½" Generator Feed & Return : 1 x 1½" Suction port : 1 x ½" Socket : Inspection Manhole : Pump Bracket			
Capacity (brim full) Litres:	960 / 948 Safe Fill	Weight Laden (kg):	1413
Capacity (brim full) Gallons:	210	Weight Unladen (kg):	550
Dimension Length (mm):	1407	Inner Tank Material (thickness):	3mm
Dimension Width (mm):	1150	Bund Material (thickness):	3mm
Dimension Height (mm):	1320	Design Approvals:	TAN 09065
Cabinet Dimensions (mm) Opening Size:	To suit Honda pump kit	Design Standards:	UN Model Regulations, Chapter 6.5