










# Specification Sheet

Description *TransCube Global* *10TCG*



The TransCube Global 10TCG is a compact, transportable, bunded diesel fuel storage tank that is ideal, compact and can be transported easily full of fuel.

The 960 litre tank quickly and easily supplies fuel where and when it is needed. Listed below are the specifications for this tank:

-  **Access manway:** allows easy access to inner tank for inspection and routine maintenance
-  **Lifting eyes:** four lifting eyes for easy handling (empty/full)
-  **110% bunded:** weatherproof bund ensures safe and environmentally complaint transport and storage
-  **Fuel equipment cabinet:** secure lockable access hatch to house pumps (electric and hand), and feed and return connections for up to 3 generators
-  **Protective galvanized stack/lifting corner plates:** protecting from damage to tank paintwork and details
-  **Mobility:** this model can be transported full of diesel without the need for ADR driver training
-  **Full load lifting eyes:** forklift pockets designed to allow handling of the Transcube Global full of fuel
-  **Internal baffles:** designed to maximise stability and safety when handling the tank full of fuel
-  **Stackable:** size to stack inside shipping containers and across truck beds providing economical transportation.

## Specifications

Standard Tank Fittings: 3" Fill Point : 2" Fill Point : Gauge : Pressure Vacuum Vent : Breather Vent : 1 x ¾" Pump Feed : 1 x ½" Generator Feed & Return : 1 x 1½" Suction port : 1 x ½" Socket : Inspection Manhole : Pump Bracket			
<b>Capacity (brim full) Litres:</b>	960 / 948 Safe Fill	<b>Weight Laden (kg):</b>	1413
<b>Capacity (brim full) Gallons:</b>	215	<b>Weight Unladen (kg):</b>	550
<b>Dimension Length (mm):</b>	1153	<b>Inner Tank Material (thickness):</b>	3mm
<b>Dimension Width (mm):</b>	1152	<b>Bund Material (thickness):</b>	3mm
<b>Dimension Height (mm):</b>	1318	<b>Design Approvals:</b>	TAN 09065
<b>Cabinet Dimensions (mm) Opening Size:</b>	To suit standard pump kit	<b>Design Standards:</b>	UN IBC 31A, TAN09062