

# **Specification Sheet**

Description Fuelchief Container Tank FP69



Fuelchief's FP Series range of double skinned diesel storage container tanks have been designed to meet the most stringent environmental standards and to operate in the most severe conditions. Our Fuelchief self-bunded container tanks are designed to be durable and for situations where the tank will be subject to frequent relocation and where increased lifetime is of importance.

Below are the benefits and features of this tank:

- Self-contained, bunded (double wall) design with any spills contained in the unit
- Container corner castings for ease of transportation, CSC Plated
- Constructed using COR-TEN® (350mpa) steel to resist corrosion
- Full under tank visibility
- Permanent ladder and platform complete with kick-boards for ease of inspection and access ladder can be fitted to either side
- 600mm manway to primary tank
- 80mm fill line with ball valve, camlock and dust cap
- 80mm suction line with anti-syphon valve
- ▼ 50mm suction line with anti-syphon valve
- 80mm free to air vent with all-weather cap
- High level alarm (Australia only)
- Primary tank comes with graduated fluid level dipstick
- Interstitial space integrity management system utilizing dipstick
- Interstitial space supplied with emergency relief vent
- Water collection well complete with evacuation pipe
- Front mounted security doors with container lock handles
- Pump bay with spill containment, earthing point and drain points\*.
- Jotun marine grade polyurethane paint 200um (white)
- Statutory signage for your region
- Warranty: 5 years structural, 1 year valves.
- Other sizes available



Ext Dimensions (L,W,H)	Capacity (total)	Capacity (SFL)	Weight (empty)
12192 x 2438 x 2896mm	69,000L	62,100L	13,000kg
Design Standards		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

\*Some models

AUSTRALIA : 1300 899 038 NEW ZEALAND : (03) 384 2380



## Other models available on request

#### **FP12 Specifications**

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
2991 x 2438 x 2896mm	11,700L	10,530L	FP12
Design Standard		Inner Tank	Outer Tank

## FP18 Specifications (no pump bay)

Ext Dimensions (l,w,h)	Capacity (total)	Capacity (SFL)	Model Number
2991 x 2438 x 2896mm	17,700L	15,930L	FP18
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

## **FP30 Specifications**

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
6058 x 2438 x 2896mm	30,500L	27,450L	FP30
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

## FP36 Specifications (no pump bay)

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
6058 x 2438 x 2896mm	36,700L	33,030L	FP36
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

## FP75 Specifications (no pump bay)

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
12192 x 2438 x 2896mm	74,800L	67,320L	FP75
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

## **FP84 Specifications**

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Weight (empty)
14630 x 2438 x 2896mm	83,700L	75,330L	FP84
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

#### FP90 Specifications (no pump bay)

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
14630 x 2438 x 2896mm	90,000L	81,000L	FP90
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940, AS1657		6mm	6mm

AUSTRALIA : 1300 899 038 NEW ZEALAND : (03) 384 2380



## **FP94 Specifications**

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
14630 x 2438 x 3200mm	94,000L	84,600L	FP94
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

# FP100 Specifications (no pump bay)

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
14630 x 2438 x 3200mm	100,000L	90,000L	FP100
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

## **FP107 Specifications**

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
14630 x 2438 x 3635mm	106,800L	96,120L	FP107
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940, AS1657		6mm	6mm

# FP116 Specifications (no pump bay)

Ext Dimensions (I,w,h)	Capacity (total)	Capacity (SFL)	Model Number
14630 x 2438 x 3635mm	115,700L	104,130L	FP116
Design Standard		Inner Tank	Outer Tank
AS1692, AS1940,	AS1657	6mm	6mm

AUSTRALIA : 1300 899 038 NEW ZEALAND : (03) 384 2380