

# Specification Sheet

Description **Fuelchief Container Tank** **FT68**



Fuelchief's FT Series range of double skinned diesel storage container tanks have been designed to meet the most stringent environmental standards and to operate in the most severe conditions. Our Fuelchief self-bunded container tanks are designed to be durable and for situations where the tank will be subject to frequent relocation and where increased lifetime is of importance.

Below are the benefits and features of this tank:

- ♥ Self-contained, bunded (double wall) design with any spills contained in the unit
- ♥ Container corner castings for ease of transportation, CSC Plated
- ♥ Constructed using COR-TEN® (350mpa) steel to resist corrosion
- ♥ Permanent ladder and platform complete with kick-boards for ease of inspection and access – ladder can be fitted to either side
- ♥ 750mm manway to primary tank
- ♥ 80mm fill line with ball valve, camlock and dust cap
- ♥ 80mm suction line with anti-syphon valve
- ♥ 80mm free to air vent with all-weather cap
- ♥ High level alarm (Australia only)
- ♥ Primary tank comes with graduated fluid level dipstick
- ♥ Interstitial space integrity management system utilizing dipstick
- ♥ Interstitial space supplied with emergency relief vent
- ♥ Water collection well complete with evacuation pipe
- ♥ Front mounted security doors with container lock handles
- ♥ Pump bay with spill containment and removable ventilation panels for farm tank applications, earthing point and drain points.
- ♥ Hempel marine grade polyurethane paint 200um (white)
- ♥ Statutory signage for your region
- ♥ Warranty: 3 years structural, 1 year valves.



Ext Dimensions (L,W,H)	Capacity (total)	Capacity (SFL)	Weight (empty)
12192 x 2438 x 2896mm	67,400	61,900L	15,000kg
Design Standards		Inner Tank	Outer Tank
AS1692, AS1940, AS1657		6mm	6mm

