

# Specification Sheet

Description **TransCube** **20TCGCAB**

The TransCube 20TCGCAB is a fully bunded (steel in steel) tank that ensures environmental compliance with EPA Guidelines. EPA Approved IBC means (Intermediate Bulk Container) and that it is approved for the transport of diesel fuel.



- ✔ 2000 litre model can be transported full of diesel without the need for ADR driver training.
- ✔ Featuring a large 700mm deep lockable cabinet to house all pumps and equipment
- ✔ Easily stacked 2 high (full), 3 high (empty) to reduce storage space requirements.
- ✔ Access manhole for maintenance and inspection of inner tank.
- ✔ Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the TransCube 20TCGCAB full of fuel.
- ✔ Secure lockable access hatch to house pumps (electric and hand!) and feed and return connections for up to 3 generators.
- ✔ Ability to supply fuel for up to 3 generators and refuel plant machinery all at the same time.
- ✔ Sized to stack inside shipping containers and across truck beds providing economical transportation.
- ✔ Protective galvanised framework preventing damage to tank, paintwork and decals.

Specifications			
Standard Tank Fittings: 3" Fill Point : 2" Fill Point : Gauge : Pressure Vacuum Vent : Breather Vent : 1 x ¾" Pump Feed : 1 x ½" Generator Feed & Return : 4 x 1½" Sockets : 1 x ½" Socket : Inspection Manhole : Pump Bracket			
Capacity (brim full) Litres:	2000 / 1940 safe fill	Weight Laden (kg):	2695
Capacity (brim full) Gallons:	440	Weight Unladen (kg):	895
Dimension Length (mm):	2280	Inner Tank Material (thickness):	3mm
Dimension Width (mm):	1550	Bund Material (thickness):	3mm
Dimension Height (mm):	1320	Design Approvals:	TAN 09066
Cabinet Dimensions (mm) Opening Size:	700mm	Design Standards:	UN Model Regulations, Chapter 6.5