

Specification Sheet

Description **TransCube** **30TCGCAB**



The TransCube 30TCGCAB allows you to extend the run times of your diesel-powered equipment and fuel more effectively. Below are some key features of this model:

- ✔ 3000 litre model can be transported full of diesel without the need for ADR driver training.
- ✔ Featuring a large 700mm deep lockable cabinet to house all pumps and equipment
- ✔ Easily stacked 2 high (full), 3 high (empty) to reduce storage space requirements.
- ✔ Access manhole for maintenance and inspection of inner tank.
- ✔ Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the TransCube 30TCGAB full of fuel.
- ✔ Secure lockable access hatch to house pumps (electric and hand!) and feed and return connections for up to 3 generators.
- ✔ Ability to supply fuel for up to 3 generators and refuel plant machinery all at the same time.
- ✔ Sized to stack inside shipping containers and across truck beds providing economical transportation.
- ✔ Protective galvanised framework preventing damage to tank, paintwork and decals.

Specifications			
Standard Tank Fittings: 3" Fill Point: 2" Fill Point : Gauge : Pressure Vacuum Vent : Breather Vent : 1 x 3/4" Pump Feed : 1 x 1/2" Generator Feed & Return : 4 x 1 1/2" Sockets : 1 x 1/2" Socket : Inspection Manhole : Pump Bracket			
Capacity (brim full) Litres:	3000	Weight Laden (kg):	3776
Capacity (brim full) Gallons:	660	Weight Unladen (kg):	1076
Dimension Length (mm):	3000	Inner Tank Material (thickness):	3mm
Dimension Width (mm):	1550	Bund Material (thickness):	3mm
Dimension Height (mm):	1320	Design Approvals:	TAN 09067
Cabinet Dimensions (mm) Opening Size:	To suit Honda pump kit	Design Standards:	UN Approval 31A