

# Specification Sheet

Description                      *TransCube*                      *20TCG*



The TransCube 20TCG is a fully bunded storage tank that reduces storage space requirements.

Approved for transport under a UN Approval, this 2,000 Litre tank is uniquely designed to provide you with hassle-free fuelling. Listed below are the specifications for this tank:

- 🔴 2000 litre model can be transported full of diesel without the need for ADR driver training.
- 🔴 Easily stacked 2 high (full), 3 high (empty) to reduce storage space requirements.
- 🔴 Access manhole for maintenance and inspection of inner tank.
- 🔴 Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the TransCube Global 20TCG full of fuel.
- 🔴 Secure lockable access hatch to house pumps (electric and hand!) and feed and return connections for up to 3 generators.
- 🔴 Ability to supply fuel for up to 3 generators and refuel plant machinery all at the same time.
- 🔴 Sized to stack inside shipping containers and across truck beds providing economical transportation.
- 🔴 Protective galvanised framework preventing damage to tank, paintwork and decals.

Specifications			
Standard Tank Fittings: 3" Fill Point: 2" Fill Point: Gauge: Pressure Vacuum Vent: Breather Vent: 1 x 3/4" Pump Feed: 1 x 1/2" Generator Feed & Return: 4 x 1 1/2" Sockets: 1 x 1/2" Socket: Inspection Manhole: Pump Bracket			
<b>Capacity (brim full) Litres:</b>	2000	<b>Weight Laden (kg):</b>	2695
<b>Capacity (safe fill) Litres:</b>	1940	<b>Weight Unladen (kg):</b>	895
<b>Dimension Length (mm):</b>	2280	<b>Inner Tank Material (thickness):</b>	3mm
<b>Dimension Width (mm):</b>	1150	<b>Bund Material (thickness):</b>	3mm
<b>Dimension Height (mm):</b>	1320	<b>Design Approvals:</b>	TAN 09066
<b>Cabinet Dimensions (mm) Opening Size:</b>	700mm	<b>Design Standards:</b>	UN Model Regulations, Chapter 6.5

