

# Specification Sheet

Description **TransCube Global** **30TCG**



The TransCube Global 30TCG is a fully bunded storage tank that reduces storage space requirements.

Approved for transport under ADR Regulations, this 3,000 Litre tank is uniquely designed to provide you with hassle-free fuelling. Listed below are the specifications for this tank:

- ✔ 3000 litre model can be transported full of diesel without the need for ADR driver training
- ✔ Featuring a large 700mm deep lockable cabinet to house all pumps and equipment
- ✔ Easily stacked 2 high (full), 3 high (empty) to reduce storage space requirements
- ✔ Access manhole for maintenance and inspection of inner tank
- ✔ Full load lifting eyes, forklift pockets and internal baffles designed to allow handling of the TransCube Global 30TCG full of fuel
- ✔ Secure lockable access hatch to house pumps (electric and hand!) and feed and return connections for up to 3 generators
- ✔ Ability to supply fuel for up to 3 generators and refuel plant machinery all at the same time
- ✔ Sized to stack inside shipping containers and across truck beds providing economical transportation
- ✔ Protective galvanised framework preventing damage to tank, paintwork and decals

Specifications			
Standard Tank Fittings: 3" Fill Point: 2" Fill Point: Gauge: Pressure Vacuum Vent: Breather Vent: 1 x 3/4" Pump Feed: 1 x 1/2" Generator Feed & Return: 4 x 1/2" Sockets: 1 x 1/2" Socket: Inspection Manhole: Pump Bracket			
<b>Capacity (brim full) Litres:</b>	3000	<b>Weight Laden (kg):</b>	3691*
<b>Capacity (safe fill) Litres:</b>	2940	<b>Weight Unladen (kg):</b>	1013
<b>Dimension Length (mm):</b>	2300	<b>Design Approvals:</b>	TAN 09064, UN IBC 31A, UL142
<b>Dimension Width (mm):</b>	1550	<b>Cabinet Dimensions (mm) Opening Size:</b>	To suit standard pump configurations
<b>Dimension Height (mm):</b>	1320	<b>Design Standards:</b>	UN Model Regulations, Chapter 6.5

\*Specific gravity of diesel taken as 0.9 for this calculation

