



Specification Sheet

Description **Fuelchief Utecube Express 250** Part No: **FCAUT250**



The Utecube range of aluminium tanks takes your refuelling needs to the next level. Excellent durability for the toughest of conditions and locally built out of the very best materials, the Utecube will last the distance.



Standard features:

- ♥ Larger range of pump options to suit your application
- ♥ High grade aluminium for extra durability
- ♥ Internal surge baffles for safe transport of fuel
- ♥ Deck runners for base protection and for securing to vehicle
- ♥ Full load lifting eyes for easier placement on site
- ♥ Pressure tested to ensure quality and compliance
- ♥ 12 month warranty

Optional extras:

- ♥ Clear bowl filters
- ♥ Range of mechanical and digital flowmeters
- ♥ Shrouded sight tubes
- ♥ Hose reels
- ♥ Key locking filler cap

Specifications			
Standard Tank Fittings: 2" filler cap, 1" suction port, 3 x lifting eyes, 2 x base runners, drain bung, nozzle stow			
Capacity (brim full) Litres:	250	Weight Laden (kg):	270
Dimension Length (mm):	928	Weight Unladen (kg):	45
Dimension Width (mm):	650	Tank Material (thickness):	4mm
Dimension Height (mm):	460	Pump Flow rates	45-60 LPM
Part Number:	FCAUT250	Hose Length	1" x 4m

