



DC50 BASIC

ONSITE REFUELLING MADE EASY

The **Basic package** has got everything needed for the client who 'just wants to pump fuel' quickly and with no fuss. This package features a proven 230v Italian Piusi bowser pump system with a mechanical display for easy recording of fuel pumped. A no complex, ready-to-use, the DC25 Basic package is a great economical choice and at a price that comes in well under budget!

WHAT ARE THE BENEFITS FOR YOUR BUSINESS?



Safe Refuelling, Easy & Compliant

The DC50 is a fully compliant double-skinned 5,000 litre tank boasting a very secure pump cabinet to keep your pump and hoses neat and tidy and away from would-be thieves.



Save Time

Onsite fuel will reduce refuelling labour time by 100's of hours per year. No more waiting in queues to refuel or to pay. Just refuel onsite and you're ready for tomorrow.



Low Maintenance

The innovative design of the DC Series tanks means no internal bracing (no safety risks) and simple condensation catchment and recovery.



Saves Money

Onsite fuel saves money. Having a depot tank will save you money on every litre of fuel and prevent unnecessary extra purchases from service stations.



Greater Control

It's never been a better time to get your business costs under control and being in control of your fuel costs makes sense.



Easy Refuelling

Open the cabinet and lift the nozzle to activate the pump making it very easy to fill up your diesel-powered machinery without delays.



The **DC50** is the tank that sits in half a car space and takes up less than 3.5m². Occupying such a small footprint makes it a great solution for those operations that have limited room available, yet still need fast and reliable access to fuel.

Our most popular model comes complete with tank vent, contents gauge and dipstick. The sloping floor and water suction port ensures easy water catchment and removal. Below are some of the key features of this tank:

- 🔧 4,629 SFL model with full height cabinet to house all pumps and equipment
- 🔧 3-way door locking system and anti-levering design for extra security
- 🔧 Cabinet has access hatch through roof to allow safe servicing of tank vent
- 🔧 Hempel C4-High Marine grade paint system
- 🔧 Spill sump in cabinet base to contain spillage
- 🔧 Improved inner tank design with no internal bracing for safe servicing
- 🔧 Sloped floor in inner tank for better water catchment and recovery
- 🔧 Water inspection and suction port housed under lockable hatch
- 🔧 Large access manhole for maintenance and inspection of inner tank
- 🔧 Extra feed and return ports for running auxiliary equipment
- 🔧 Lockable fill point with integrated dipstick
- 🔧 Offset fill pipe with Todo Dry-Break coupling for rapid refuelling
- 🔧 1100 LPM rated & approved overfill prevention valve
- 🔧 Base of tank sealed in an anti-rust underseal

SPECIFICATIONS

Dimensions (mm) (W x L x H)	1150 x 2996 x 2550
Capacity (Total)	5,000 Litres
Capacity (SFL)	4,629 Litres
Design Approval	TNK 15024
Design Standard	AS1692
Weight (Empty)	1600 Kg

COMPONENTS:



DELIVERY HOSE OPTIONS:



HOSE



HOSE REEL



HOSE TOWER

DC50BAS4M	Fuelchief DC50 Diesel Tank (4629 SFL) with Cube 70 Bowser, Flow Meter, 4m Hose & Auto Nozzle
DC50BAS10H	Fuelchief DC50 Diesel Tank (4629 SFL) with Cube 70 Bowser, Flow Meter, 10m Hose Reel & Auto Nozzle
DC50BAS15H	Fuelchief DC50 Diesel Tank (4629 SFL) with Cube 70 Bowser, Flow Meter, 15m Hose Reel & Auto Nozzle
DC50BASHT	Fuelchief DC50 Diesel Tank (4629 SFL) with Cube 70 Bowser, Flow Meter, 3m Hose Tower with 7m Hose & Auto Nozzle