



DC50 INDUSTRY

FAST REFUELLING,
TRACKED IN REAL-TIME

The **Industry package** includes the unique Sapphire Online fuel management system and is for the operator who is serious about every drop used. This is the premium option when it comes to monitoring your fuel with advanced real-time technology. The Industry package is perfect if you have a fleet of vehicles on one site or across multiple sites and require accurate and real-time data in one place.

This package is for users who have both on-road and off-road vehicles which are re-fuelling at both a company yard tank and retail fuel outlets. The Sapphire Online fuel management system is easy to use and can utilise existing fuel cards already allocated within the company. Other options include key tags, thus providing you with accurate, real-time reporting from any device that is connected to the internet.

WHAT ARE THE BENEFITS FOR YOUR BUSINESS?



Space Saver

The DC50 footprint is so compact, it fits in half a car parking space; ideal for businesses who are after a compact and out of the way solution.



Save Time

Onsite fuel will reduce refuelling labour time by 100's of hours per year. No more waiting in queues to refuel or to pay. Just refuel onsite and you're ready for tomorrow.



Low Maintenance

The innovative design of the DC Series tanks means no internal bracing (no safety risks) and simple condensation catchment and recovery.



Saves Money

Onsite fuel saves money. Having a depot tank will save you money on every litre of fuel and prevent unnecessary extra purchases from service stations.



Greater Control

It's never been a better time to get your business costs under control, and the Fuelchief DC50 Industry package allows you to do this effortlessly.



Stop Fuel Theft

Fuel theft is a big problem nationwide. Our Industry package is the perfect option, restricting access to only those supplied with a user keys or PINs.



The **DC50** is the tank that sits in half a car space and takes up less than 3.5m². Occupying such a small footprint makes it a great solution for those operations that have limited room available, yet still need fast and reliable access to fuel.

Our most popular model comes complete with tank vent, contents gauge and dipstick. The sloping floor and water suction port ensures easy water catchment and removal. Below are some of the key features of this tank:

- 🔴 4,629 SFL model with full height cabinet to house all pumps and equipment
- 🔴 3-way door locking system and anti-levering design for extra security
- 🔴 Cabinet has access hatch through roof to allow safe servicing of tank vent
- 🔴 Hempel C4-High Marine grade paint system
- 🔴 Spill sump in cabinet base to contain spillage
- 🔴 Improved inner tank design with no internal bracing for safe servicing
- 🔴 Sloped floor in inner tank for better water catchment and recovery
- 🔴 Water inspection and suction port housed under lockable hatch
- 🔴 Large access manhole for maintenance and inspection of inner tank
- 🔴 Extra feed and return ports for running auxiliary equipment
- 🔴 Lockable fill point with integrated dipstick
- 🔴 Offset fill pipe with Todo Dry-Break coupling for rapid refuelling
- 🔴 1100 LPM rated & approved overfill prevention valve
- 🔴 Base of tank sealed in an anti-rust underseal

Dimensions (mm) (W x L x H)

1150 x 2996 x 2550

Capacity (Total)

5,000 Litres

Capacity (SFL)

4,629 Litres

Design Approval

TNK 15024

Design Standard

AS1692

Weight (Empty)

1600 Kg

COMPONENTS:



DELIVERY HOSE OPTIONS:



HOSE



HOSE REEL



HOSE TOWER

DC50IND6M

Fuelchief DC50 Diesel Tank (4629 SFL) with 100LPM High Flow Pump Kit, Sapphire Online FMS, 6m Hose & Auto Nozzle

DC50IND10H

Fuelchief DC50 Diesel Tank (4629 SFL) with 100LPM High Flow Pump Kit, Sapphire Online FMS, 10m Hose Reel & Auto Nozzle

DC50IND15H

Fuelchief DC50 Diesel Tank (4629 SFL) with 100LPM High Flow Pump Kit, Sapphire Online FMS, 15m Hose Reel & Auto Nozzle

DC50INDHT

Fuelchief DC50 Diesel Tank (4629 SFL) with 100LPM High Flow Pump Kit, Sapphire Online FMS, 3m Hose Tower with 7m Hose & Auto Nozzle