



DC50 BASIC PLUS

I JUST WANT TO PUMP FUEL
- AND FAST

The **Basic Plus package** is for the client who wants extra flow for faster re-fuelling. This package features the Piusi E120 Italian pump system with an impressive flow rate of 100LPM, high-quality Donaldson filter and a mechanical display for easy recording of fuel pumped. This is a high-value yet economical choice for customers and at a price point that is of an advantage.

WHAT ARE THE BENEFITS FOR YOUR BUSINESS?



Space Saver

The DC50 footprint is so compact, it fits in half a car parking space; ideal for businesses who are after a compact and out of the way solution



Saves Money

Onsite fuel saves money. Having a depot tank will save you money on every litre of fuel and prevent unnecessary extra purchases from service stations



Minimise Downtime

The 'Basic-Plus' options allows fast refuelling. The fast-flow Italian Piusi pump can deliver up to 100 litres per minute which is approximately three time faster than your standard service station.



Stop Fuel Theft

Fuel theft is a big problem nationwide. The 'tri-latch' systems ensures that the full height access door can be securely locked each night preventing would be fuel thieves.



Low Maintenance

The innovative design of the DC Series tanks means no internal bracing (no safety risks) and simple condensation catchment and recovery.



Save Time

Onsite fuel will reduce refuelling labour time by 100's of hours per year. No more waiting in queues to refuel or to pay. Just refuel and you're ready for tomorrow.



The **DC50** is the tank that sits in half a car space and takes up less than 3.5m². Occupying such a small footprint makes it a great solution for those operations that have limited room available, yet still need fast and reliable access to fuel.

Our most popular model comes complete with tank vent, contents gauge and dipstick. The sloping floor and water suction port ensures easy water catchment and removal. Below are some of the key features of this tank:

- 🔧 4,629 SFL model with full height cabinet to house all pumps and equipment
- 🔧 3-way door locking system and anti-levering design for extra security
- 🔧 Cabinet has access hatch through roof to allow safe servicing of tank vent
- 🔧 Hempel C4-High Marine grade paint system
- 🔧 Spill sump in cabinet base to contain spillage
- 🔧 Improved inner tank design with no internal bracing for safe servicing
- 🔧 Sloped floor in inner tank for better water catchment and recovery
- 🔧 Water inspection and suction port housed under lockable hatch
- 🔧 Large access manhole for maintenance and inspection of inner tank
- 🔧 Extra feed and return ports for running auxiliary equipment
- 🔧 Lockable fill point with integrated dipstick
- 🔧 Offset fill pipe with Todo Dry-Break coupling for rapid refuelling
- 🔧 1100 LPM rated & approved overfill prevention valve
- 🔧 Base of tank sealed in an anti-rust underseal

Dimensions (mm) (W x L x H)

1150 x 2996 x 2550

Capacity (Total)

5,000 Litres

Capacity (SFL)

4,629 Litres

Design Approval

TNK 15024


Design Standard

AS1692

Weight (Empty)

1600 Kg

COMPONENTS:



DELIVERY HOSE OPTIONS:



HOSE



HOSE REEL



HOSE TOWER

DC50BAP6M

Fuelchief DC50 Diesel Tank (4629 SFL) 100LPM High Flow Pump Kit, Flow Meter, 6m Hose & Auto Nozzle

DC50BAP10H

Fuelchief DC50 Diesel Tank (4629 SFL) with 100LPM High Flow Pump Kit, Flow Meter, 10m Hose Reel & Auto Nozzle

DC50BAP15H

Fuelchief DC50 Diesel Tank (4629 SFL) with 100LPM High Flow Pump Kit, Flow Meter, 15m Hose Reel & Auto Nozzle

DC50BAPHT

Fuelchief DC50 Diesel Tank (4629 SFL) with 100LPM High Flow Pump Kit, Flow Meter, 3m Hose Tower with 7m Hose & Auto Nozzle